



Item number Consumption **Raw material** Application

5 kg: LO500500BR24 10 kg: LW100100BR24 Density of 18 kg/m³ is sufficient 100% wool sustainable, durable, recyclable, without synthetic additives Window- and hollow space insulation, Wooden construction

PRODUCT DESCRIPTION

- Carded wool fleece for filling joints and cracks between beams, walls and hollow spaces on windows and doors.
- Darning wool is also suitable for **roof windows** in the roofing frame.

WOOL PROTECTION

- IONIC PROTECT® biocide-free wool protection, long-term tested by EAD/CUAP standards and patented procedure
- Is a slight alteration of the molecular protein structure of the wool fibre through a plasma-ion treatment. This specific process is unique as it permanently prevents the wool from being a nutritional source for wool parasites
- Through the wool protection, our products have an **unlimited shelf-life**. •



INSTALLATION

Fill up the hollow spaces with a scrapper or spread the wool fleece manually.

PROPERTIES



Air purification







Sustainable



Wool protection



÷











DIMENSIONS 5 or 10kg per packaging unit (PU)

Article	Thickness (mm)	Width (mm)	Lengths (mm)	ltem /PU	kg PU
LW05	-	-	-	1	5,00
LW10	-	-	-	1	10,00

TECHNICAL DATA

European technical approval	ETA-07/0214
Nature Plus®	0103-1006-099-1
Thermal conductivity $\mathbf{\lambda}_{tr}$	0,038 W/mK
Fire behaviour according to EN 13501-1 from 18kg/m ³	D-s2, d0; CH: RF3
Vapour diffusion resistance factor μ	1
Specific heat capacity c	1760 J/kgK
Mould growth intensity according to EN ISO 846	0

ECOLOGICAL PARAMETERS Compliant with the NaturePlus® Life cycle assessment ISOLENA

Use of non-renewable primary energy without the non-renewa- ble primary energy carriers used as raw material (PENRE [MJ, lower calorifi c value])	23,44	MJ / kg
Global warming potential Total of GHG emissions and CO2 storage (GWP 100 total)	0,83	kg CO _{2-äquiv.} / kg
Acidifi cation potential of soil and water (AP)	4,63E-03	kg SO _{2-äquiv.} / kg
Potential for the formation of tropospheric ozone (POCP)	8,04E-04	kg C ₂ H _{4-äquiv.} / kg
Eutrophication potential (EP)	2,08E-03	kg PO ³ kg













SOLENA NEWSLETTER

three weeks

Subscribe now!





ISOLENA NATURFASERVLIESE GMBH | KLOSTERSTRASSE 20 | AT-4730 WAIZENKIRCHEN TEL +43 7277 2496-198 | OFFICE@ISOLENA.AT | ISOLENA.AT